

Produktinformation

ISDT SP2425 24V SMART POWER NETZGERÄT 600W MIT BATTGO[®]

Art-Nr.: Robbe-SP2425 / GTIN: 6,97E+12 / Marke: [ISDT](#)

130,00CHF

zzgl. Versand

 Produkt lagernd, sofort versandfertig.



DUAL USB OUTPUT

Dual usb-powered output maximum current 2A+2A,It can charge two mobile phones at the same time.



Produktinformation

ALUMINIUM ALLOY SHELL
Integrated aluminum magnesium alloy shell, sturdy and durable.



- Power on
- Connect to the BattGO device
- Turn on 25% power
- Turn on 50% power
- Turn on 75% power
- Turn on 100% power
- Error



Indicator light



USB port



Model	SP2425	SP2425
Input voltage range	AC 100-240V(50/60Hz)	AC 100-240V(50/60Hz)
Max input current	5A	5A
Output voltage range	DC 24V	DC 24V
Rated output current	25A	25A
Output power	600W	600W
USB output	5V/2A	5V/2A
Efficiency	>93% @230Vac	>93% @230Vac
Active PFC	Yes	Yes
Power factor	>0.95	>0.95
Output interface	EC3 (Compatible with EC3)	EC3 (Compatible with EC3)
Start delay	0.3 seconds	0.3 seconds
Working temperature	-20~45°C	-20~45°C
Working humidity	0~90% RH, no condensation	0~90% RH, no condensation
Size	221*100*63mm	221*100*63mm
Weight	1.4kg	1.4kg

Beschreibung "ISDT SP2425 24V SMART POWER NETZGERÄT 600W MIT BATTGO®"

Specs:

- Input voltage range: AC 100-240V(50/60Hz)
- Max input current: 6A
- Output voltage range: DC 24V
- Rated output current: 25A
- Output current: 600W
- USB output: 5V/2A
- Efficiency: >93% @230Vac
- Active PFC: YES Power factor > 0.95
- Output interface: EC3 (Compatible with EC3)
- Start delay: 0.3 seconds
- Working temperature: -20-45°C
- Working humidity: 0-90% RH, no condensation
- Size: 221*100*63mm Weight: 1.4Kg

Technische Daten Eingangssp.: AC 100-240V Ausgangssp.: DC 24V Max. Ladestrom: 25 A